



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No: 950/1-CPR/2014

Substrate: Mortar M1 and Anodised Aluminium

Primer: No primer

| 1. Identification Code | Everbuild 950 Silicone Sealant; |
|---|---|
| | |
| | Codes: 950WE / FP950WE |
| 2. Type, Batch and/or Serial Number | - For batch number - see packaging |
| 3. Intended use | Sealant for non-structural use in joints in buildings |
| | and pedestrian walkways Part 1: Sealants for Façade |
| | elements |
| 4. Manufacturer | Everbuild Building Products Itd, Site 41, Cross Green |
| | Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW |
| 5. Authorised Representative | Not Applicable |
| 6. Assessment and Verification of Constancy | System 3 |
| of Performance | |
| 7. Notified Body and Tasks | SKZ Notified Body No. 1213 |
| 8. European Technical Assessment | Not Applicable |
| 9. Declared Performance | TO EN15651-1 (2012) |
| Туре | F EXT-INT-CC |
| Classification | F25LM |
| Reaction to Fire | Class E |



Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

| | Webblief Williefelandicelan |
|---|-----------------------------|
| Loss of Volume ISO10563 | ≤10% |
| Resistance to flow ISO7390 | ≤3 mm |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | NF |
| Adhesion/cohesion properties (-30°C) | ≤0.9 MPa |
| Durability ISO 8340, ISO 9047 and ISO 10590 | Pass |

Substrate: Glass

Primer: No primer

| 1. Identification Code | Everbuild 950 Silicone Sealant; |
|--|---|
| | Codes: 950WE / FP950WE |
| 2. Type, Batch and/or Serial Number | - For batch number - see packaging |
| 3. Intended use | Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing elements |
| 4. Manufacturer | Everbuild Building Products ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW |
| 5. Authorised Representative | Not Applicable |
| 6. Assessment and Verification of Constancy of Performance | System 3 |
| 7. Notified Body and Tasks | SKZ Notified Body No. 1213 |
| 8. European Technical Assessment | Not Applicable |
| 9. Declared Performance | TO EN15651-2 (2012) |



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

| | website: www.everbuild.co.uk |
|---|------------------------------|
| Туре | G-CC |
| Classification | G25LM |
| Reaction to Fire | Class E |
| Loss of Volume ISO10563 | ≤10% |
| Resistance to flow ISO7390 | ≤3 mm |
| Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590 | NF |
| Adhesion/cohesion properties after exposure to heat, water and artificial light ISO 11431 | NF |
| Elastic recovery ISO 7389 | ≥60% |
| Adhesion/cohesion properties (-30°C) ISO 8339 modified | ≤0.9 MPa |
| Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340 | NF |
| Durability ISO 8340, ISO 9047 and ISO 10590 | Pass |
| | 1 |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical P.R. Thomas – Technical Manager

Dated: Leeds, 10/6/14