



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: S50/1-CPR/ 2014

1. Identification Code	EVERFLEX Silicone S50 Codes: S50
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-1 (2012)
Type	F EXT-INT-CC
Classification	F20LM
Reaction to Fire	Class F
Loss of Volume ISO10563	≤10%



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
 Cross Green Industrial Estate, Leeds, LS9 0SW
 Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
 Fax: +44 (0) 113 240 0024
 e-mail: info@everbuild.co.uk
 website: www.everbuild.co.uk

Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties (-30°C)	NF
Durability	Pass

1. Identification Code	EVERFLEX Silicone S50 Codes: S50
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing elements
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-2 (2012)
Type	G-CC
Classification	G20LM



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
 Cross Green Industrial Estate, Leeds, LS9 0SW
 Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
 Fax: +44 (0) 113 240 0024
 e-mail: info@everbuild.co.uk
 website: www.everbuild.co.uk

Reaction to Fire	Class F
Loss of Volume ISO10563	≤10%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties after exposure to heat, water and artificial light ISO 11431	NF
Elastic recovery ISO 7389	≥60%
Adhesion/cohesion properties (-30°C) ISO 8339 modified	NF
Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340	NF
Durability	Pass

1. Identification Code	EVERFLEX Silicone S50 Codes: S50
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
 Cross Green Industrial Estate, Leeds, LS9 0SW
 Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
 Fax: +44 (0) 113 240 0024
 e-mail: info@everbuild.co.uk
 website: www.everbuild.co.uk

of Performance	
7. Notified Body and Tasks	SKZ Notified Body No. 1213
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-3 (2012)
Type	S
Classification	XS1
Reaction to Fire	Class F
Loss of Volume ISO10563	≤20%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Action of the microorganisms : Intensity of growth ISO 846, method B	1
Durability	Pass

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 1/5/14