



**DECLARATION OF PERFORMANCE**

According to Annex III of the Regulation (EU) no 305/2011

**ARBOKOL 2150 GUN GRADE**

**DOP 2014-AR2150GG17**

**EN15651 -1: F – EXT-INT**

**Sealant for Façade Elements for exterior and interior application.**

Contact address of the manufacturer:

**Adshead Ratcliffe and Co Ltd  
Derby Road  
Belper  
Derby  
DE56 1WJ**

Verification of constancy of performance of the construction product as set out in Annex V:

The Notified Body 4ward Testing, Identification Number **NB2538**, performed the determination of the product type on the basis of type testing under System 3 and issued:

Report Number: NLR1788

The performance of the product identified is in conformity with the declared performance (see below). This Declaration of Performance is issued under the sole responsibility of the Manufacturer

A handwritten signature in black ink, appearing to read "S. Brown".

Steven Brown  
Technical Director  
Adshead Ratcliffe and Co Ltd  
25th June 2014



**ARBOKOL 2150 GUN GRADE – Declared  
Performance**



**EN 15651-1:F – EXT-INT  
CLASS – 20HM**

**Preconditioning: Method A (according to ISO  
8340)**

**Substrate: Mortar with Arbokol AG2 Porous  
Primer**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire (EN 13501)	NPD	EN15651-1:2012
Release of chemicals dangerous to the environment and health	See product Material Safety Data Sheet	
Water tightness and air tightness		
Resistance to Flow (ISO 7390)	$\leq 3$ mm	
Loss of Volume (ISO 10563)	$\leq 10$ %	
Secant Tensile Modulus at + 23 ± 2°C (ISO 8339)	$\geq 0.4$ Mpa	
Durability	Pass	