

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name:** MAXTACK PRO-50

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet**

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** pault@everbuild.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** 0044 113 240 3456 (office hours only)

**Section 2: Hazards identification****2.1. Classification of the substance or mixture**

**Classification under CHIP:** F: R11; -: R52/53; -: R67

**Classification under CLP:** Eye Irrit. 2: H319; Aquatic Chronic 3: H412; Skin Irrit. 2: H315; Flam. Liq. 2: H225; Flam. Liq. 3: H226

**Most important adverse effects:** Highly flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

**2.2. Label elements****Label elements under CLP:**

**Hazard statements:** H315: Causes skin irritation.

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark



# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 2

**Precautionary statements:** P102: Keep out of reach of children.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P273: Avoid release to the environment.  
P280: Wear protective gloves.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical attention.  
P332+313: If skin irritation occurs: Get medical advice.  
P302+352: IF ON SKIN: Wash with plenty of soap and water.  
P370+378: In case of fire: Use powder, foam or carbon dioxide for extinction.

## Label elements under CHIP:

**Hazard symbols:** Highly flammable.



**Risk phrases:** R11: Highly flammable.  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S29: Do not empty into drains.  
S2: Keep out of the reach of children.  
S16: Keep away from sources of ignition - No smoking.  
S24: Avoid contact with skin.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37: Wear suitable protective clothing and gloves.  
S43: In case of fire, use powder, foam or carbon dioxide.  
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 3

## Hazardous ingredients:

### METHYL ETHYL KETONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

### NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT - REACH registered number(s): 01-2119473851-33-XXXX

920-750-0	-	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 2: H225; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315	1-10%
-----------	---	---	--	-------

### PETROSOL D80/95

-	-	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R66; -: R67	-	1-10%
---	---	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately.  
Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be irritation of the throat.
- Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.  
Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 4

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### 8.1. DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Respiratory protection not required.

[cont...]

# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 5

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Beige

**Odour:** PETROL-LIKE

**Evaporation rate:** Fast

**Solubility in water:** Insoluble

**Viscosity:** Highly viscous

**Flash point°C:** -10

**Relative density:** 1.2 - 1.3g/cm<sup>3</sup>

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 6

## Hazardous ingredients:

### METHYL ETHYL KETONE

IPR	RAT	LD50	607	mg/kg
ORL	MUS	LD50	4050	mg/kg
ORL	RAT	LD50	2737	mg/kg

**Toxicity values:** No data available.

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1133

[cont...]

# SAFETY DATA SHEET

MAXTACK PRO-50

Page: 7

## 14.2. UN proper shipping name

Shipping name: ADHESIVES

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and 3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R11: Highly flammable.

R36: Irritating to eyes.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

[cont...]

## SAFETY DATA SHEET

MAXTACK PRO-50

Page: 8

aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.