

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	FIRE RATED FOAM CLP
--------------	---------------------

1.3. Details of the supplier of the safety data sheet

Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk

1.4. Emergency telephone number


Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	Xn; R20-40-42/43-48/20 Xi; R36/37/38 Symbols: Xn: Harmful.
Main hazards	Harmful by inhalation. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation.
2.1.2. Classification - EC 1272/2008	Flam. Aerosol 1: H222; Acute Tox. 4: H302+H332; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; STOT RE 2: H373;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	<p>Aerosols 1: H222 - Extremely flammable aerosol.</p> <p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.</p> <p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Skin Sens. 1: H317 - May cause an allergic skin reaction.</p> <p>Eye Irrit. 2: H319 - Causes serious eye irritation.</p> <p>Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p>

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

2.2. Label elements

Precautionary Statement: Prevention	<p>Carc. 2: H351 - Suspected of causing cancer .</p> <p>STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .</p> <p>P201 - Obtain special instructions before use.</p> <p>P202 - Do not handle until all safety precautions have been read and understood.</p> <p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 - Do not spray on an open flame or other ignition source.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p> <p>P251 - Do not pierce or burn, even after use.</p> <p>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p> <p>P270 - Do no eat, drink or smoke when using this product.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P272 - Contaminated work clothing should not be allowed out of the workplace.</p> <p>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P284 - [In case of inadequate ventilation] wear respiratory protection.</p>
Precautionary Statement: Response	<p>P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 - IF exposed or concerned: Get medical advice/attention.</p> <p>P312 - Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P314 - Get medical advice/attention if you feel unwell.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P330 - Rinse mouth.</p> <p>P332+P313 - If skin irritation occurs: Get medical advice/attention.</p> <p>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P337+P313 - If eye irritation persists: Get medical advice/attention.</p> <p>P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/ .</p> <p>P370+P378 - In case of fire: Use to extinguish.</p>
Precautionary Statement: Storage	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 - Store in a well-ventilated place. Keep cool.</p> <p>P405 - Store locked up.</p> <p>P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.</p>
Precautionary Statement: Disposal	<p>P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations</p>

SECTION 3: Composition/information on ingredients

3.1. Substances

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Diphenylmethanediisocyanate, isomers and homologues		9016-87-9				Xn; R20-40-42/43-48/20 Xi; R36/37/38	
Isobutane	601-004-00-0	75-28-5	200-857-2			F+; R12	
Phosphoric trichloride, reaction products with propylene oxide		1244733-77-4					
Dimethyl ether	603-019-00-8	115-10-6	204-065-8			F+; R12	
Butane	601-004-00-0	106-97-8	203-448-7			F+; R12	
Propane	601-003-00-5	74-98-6	200-827-9			F+; R12	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Diphenylmethanediisocyanate, isomers and homologues		9016-87-9				Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Acute Tox. 4: H332; Resp. Sens. 1: H334; STOT SE 3: H335; Carc. 2: H351; STOT RE 2: H373;	
Isobutane	601-004-00-0	75-28-5	200-857-2			Flam. Gas 1: H220;	
Phosphoric trichloride, reaction products with propylene oxide		1244733-77-4					
Dimethyl ether	603-019-00-8	115-10-6	204-065-8			Flam. Gas 1: H220;	
Butane	601-004-00-0	106-97-8	203-448-7			Flam. Gas 1: H220;	
Propane	601-003-00-5	74-98-6	200-827-9			Flam. Gas 1: H220;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause dermatitis. May cause irritation to skin.
Ingestion	Harmful if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance
--	---

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

5.2. Special hazards arising from the substance or mixture

to source of ignition and flash back.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Butane	WEL 8-hr limit ppm: 600	WEL 8-hr limit mg/m3: 1450
	WEL 15 min limit ppm: 750	WEL 15 min limit mg/m3: 1810
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Dimethyl ether	WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 766
	WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 958
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

Respiratory protection

Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Yellow
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	> 60 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Autoignition temperature	No data available
Explosive properties	No data available
Oxidising properties	No data available
Relative density	1.1 (H ₂ O = 1 @ 20 °C)
Partition coefficient	No data available
Viscosity	No data available
Fat Solubility	No data available
Solubility	Insoluble in water

9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

12.3. Bioaccumulative potential

--	--

Partition coefficient

	FIRE RATED FOAM CLP No data available
--	--

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

14.4. Packing group

Packing group -

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	-
Tunnel Category	(D)

IMDG

EmS Code F-D S-U

IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
-------------	---

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 2 - Precautionary Statement: Disposal. 11 - 11.1.4. Toxicological Information. 12 - 12.1. Toxicity.
----------	--

FIRE RATED FOAM CLP

Revision 1

Revision date 2015-05-20

Other information	
Text of risk phrases in Section 3	<p>15 - Regulations.</p> <p>R12 - Extremely flammable. R20 - Harmful by inhalation. R36/37/38 - Irritating to eyes, respiratory system and skin. R40 - Limited evidence of a carcinogenic effect. R42/43 - May cause sensitisation by inhalation and skin contact. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.</p>
Text of Hazard Statements in Section 3	<p>Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 4: H332 - Harmful if inhaled. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Carc. 2: H351 - Suspected of causing cancer . STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Flam. Gas 1: H220 - Extremely flammable gas.</p>
Further information	
	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>