

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : MaxTack® Ultra Clear

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

### 1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company  
Site 41  
Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds  
West Yorkshire LS9 0SW  
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

### 1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

|                          |  |  |
|--------------------------|--|--|
| Hazard statements        | : H317<br>H319<br>H412   | May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Harmful to aquatic life with long lasting effects.   |
| Precautionary statements | : P101<br><br>P102<br><b>Prevention:</b><br>P261<br><br>P273<br>P280<br><br><b>Disposal:</b><br>P501 | If medical advice is needed, have product container or label at hand.<br>Keep out of reach of children.<br><br>Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.<br>Avoid release to the environment.<br>Wear protective gloves/ eye protection/ face protection.<br><br>Dispose of contents/container in accordance with local regulation. |

Hazardous components which must be listed on the label:

- Pentamethyl piperidylsebacate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

| Chemical name<br>CAS-No.<br>EC-No.<br>Registration number   | Classification<br>(REGULATION (EC)<br>No 1272/2008)                     | Concentration<br>[%] |
|---|---|----------------------|
| 3-(trimethoxysilyl)propylamine<br>13822-56-5<br>237-511-5<br>01-2119510159-45-XXXX  | Skin Irrit.2; H315<br>Eye Dam.1; H318                                   | >= 2,5 - < 3         |
| trimethoxyvinylsilane<br>2768-02-7<br>220-449-8<br>01-2119513215-52-XXXX<br>Contains:<br>tetramethyl orthosilicate <= 0,2 %             | Flam. Liq.3; H226<br>Acute Tox.4; H332<br>STOT RE2; H373                | >= 1 - < 2,5         |
| Pentamethyl piperidylsebacate<br><br>915-687-0<br>01-2119491304-40-XXXX<br>Contains:<br>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | Skin Sens.1A; H317<br>Aquatic Acute1; H400<br>Aquatic Chronic1;<br>H410 | >= 0,25 - < 1        |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Excessive lachrymation  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects
- May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### 5.2 Special hazards arising from the substance or mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

| Components | CAS-No. | Value | Control parameters               | Basis * |
|------------|---------|-------|----------------------------------|---------|
| methanol   | 67-56-1 | TWA   | 200 ppm<br>266 mg/m <sup>3</sup> | GB EH40 |
|            |         | STEL  | 250 ppm<br>333 mg/m <sup>3</sup> | GB EH40 |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : colourless

Odour : slight

Odour Threshold : No data available

Flash point : > 93,33 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : No data available

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,05 g/cm<sup>3</sup> at 20 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

|  |   |                                       |
|--|---|---------------------------------------|
| Water solubility                       | : | insoluble                             |
| Partition coefficient: n-octanol/water | : | No data available                     |
| Viscosity, dynamic                     | : | No data available                     |
| Viscosity, kinematic                   | : | > 20,5 mm <sup>2</sup> /s<br>at 40 °C |
| Relative vapour density                | : | No data available                     |
| Evaporation rate                       | : | No data available                     |

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products : methanol

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

##### trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50: 3.540 mg/kg

### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

#### **Components:**

#### **Pentamethyl piperidylsebacate :**

Toxicity to fish : LC50: 0,97 mg/l, 96 h, Fish

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

No data available

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : 2,5 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environ- : Environmental Protection Act 1990 & Subsidiary Regulations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

mental regulation/legislation specific for the substance or mixture:

Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### 15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

### Full text of H-Statements

|      |  |
|------|--|
| H226 | Flammable liquid and vapour.                                       |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                               |
| H318 | Causes serious eye damage.   |
| H332 | Harmful if inhaled.  |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life.  |
| H410 | Very toxic to aquatic life with long lasting effects.              |

### Full text of other abbreviations

|                 |  |
|-----------------|--|
| Acute Tox.      | Acute toxicity   |
| Aquatic Acute   | Acute aquatic toxicity   |
| Aquatic Chronic | Chronic aquatic toxicity   |
| Eye Dam.        | Serious eye damage   |
| Flam. Liq.      | Flammable liquids  |
| Skin Irrit.     | Skin irritation  |
| Skin Sens.      | Skin sensitisation   |
| STOT RE         | Specific target organ toxicity - repeated exposure   |
| ADR             | Accord européen relatif au transport international des marchandises Dangereuses par Route  |
| CAS             | Chemical Abstracts Service   |
| DNEL            | Derived no-effect level  |
| EC50            | Half maximal effective concentration   |
| GHS             | Globally Harmonized System   |
| IATA            | International Air Transport Association  |
| IMDG            | International Maritime Code for Dangerous Goods  |
| LD50            | Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)   |
| LC50            | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)   |
| MARPOL          | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL             | Occupational Exposure Limit  |
| PBT             | Persistent, bioaccumulative and toxic  |
| PNEC            | Predicted no effect concentration  |
| REACH           | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## MaxTack® Ultra Clear

Revision Date 11.08.2017



BUILDING TRUST



Version 5.8

Print Date 11.08.2017

SVHC  
vPvB

Substances of Very High Concern  
Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !