

## SURVEYLINE MARKER SPRAY



Colour	Product Code	Pack Size	Box Qty
White	SURVEYWE	700ml	12
Yellow	SURVEYYELL	700ml	12
Red	SURVEYRED	700ml	12
Orange	SURVEYOG	700ml	12
Green	SURVEYGREEN	700ml	12
Blue	SURVEYBLUE	700ml	12
Black	SURVEYBK	700ml	12

### Product Description

A spray applied solvent based marking paint for general contractors/surveyors spot marking. Colour coded for gas, electric, water and cable company use. Also suitable for highlighting pot holes, machinery positions etc and for general highway maintenance, excavation sites, mining, turf marking and landscaping use. Semi permanent formula lasts at least 3 months after application under normal wear conditions. Typically, the following colours have the following applications.

- White/Yellow – General Marker
- Blue – Water
- Red – Electricity
- Green – Cablework
- Black – Covering old lines

### Benefits

- High covering power.
- Semi Permanent formula.
- Adheres to most common surfaces.
- Apply by hand or applicator.

### Areas For Use

- Highlighting holes, machine positions, fixing positions.
- Marking cable positions prior to drilling/cutting.
- Turf marking and landscaping use.
- Excavation and mining.

### Limitations

- Do not apply this product if rain is imminent (within 2 hours of application)
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice or refer to technical data sheet

### Application

- Paint designed for inverted use only.
- Shake can vigorously for 2-3 minutes after weights are heard to rattle.
- To apply by hand (remove cap, turn upside down and pull nozzle towards tin using two fingers.

- To apply using the Everbuild Survey Line hand applicator, remove cap and insert can into cradle of applicator.
- Nozzle must be cleared in any pause during use.
- To clear after use, turn can pointing nozzle up and away from user and activate for 1 or 2 seconds.

#### Health & Safety

Consult MSDS for full list of hazards.

#### Storage

Store in cool, dry conditions, between 5 and 25`C. PROTECT FROM FROST.

#### Shelf Life

12 months from date of manufacture.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*